

SOIL BUCKET HD / HD+



Soil bucket HD

Robust soil bucket with standard spill guard for heavy-duty applications. Transport guard, bolt-on teeth and reversible blade are options.

All advantages at a glance

- Short bucket base optimises break-out forces
- High-tensile HB 400 blade
- Levelling blade

Options

- Bolt-on teeth
- Transport guard
- Reversible blade

Width	Volume	Weight	2024	2024 SLT	2028-2	2028 SLT	23e	23e T	24e	2428-2	2428 SLT	2430	2430 SLT	2445 S	2628	2630	2630 SLT	2630 T SLT	3630	3650	3650 SLT	3650 T	3650 T SLT	4670	4670 Z	4670 T
1.00 m	0.40 m ³	176 kg	■	■	■	■	■		■	■	■	■	■	□	□	■	■		□	□	□					
1.20 m	0.48 m ³	187 kg	■	■	■	■	■	□	■	■	■	■	■	■	■	■	■	□	■	■	■	□	□	□		
1.30 m	0.52 m ³	198 kg	□	□	□	□	■	□	■	□	□	■	■	■	□	■	■	□	■	■	■	□	□	□		
1.40 m	0.56 m ³	209 kg	□	□	□	□	■	■	■	□	□	□	□	■	□	□	□	■	■	■	■	■	■	■	□	□
1.50 m	0.60 m ³	220 kg					□	■	■			□	□	■		□	□	■	□	■	■	■	■	■	■	■
1.60 m	0.64 m ³	231 kg					□	■	■					■				■	□	■	■	■	■	■	■	■
1.70 m	0.68 m ³	260 kg					□	□	□									□		□	□					

All major coupling options available. □ = good match ■ = perfect match

Width	Volume	Weight	5470 Z	5680 Z	5680 T	6680 Z / 6680 Z-2	6680 T / 6680 T-2	8620 T-2	9640 T-2	9660 T-2
1.80 m	0.98 m ³	353 kg	■	■	■	■	■	□		
2.00 m	1.03 m ³	375 kg	■	■	■	■	■	■	□	
2.20 m	1.19 m ³	397 kg				■	■	■	□	□
2.40 m	1.30 m ³	433 kg				□	□	■	■	■

All major coupling options available. □ = good match ■ = perfect match