

SOIL REVERSAL TILLER



The hydraulic soil reversal tiller is the reliable partner for seedbed preparation in garden landscaping. The milling blades, which rotate against the direction of travel, pick up the soil and throw it against a sieve grid. Coarse components are sieved out and buried. The soil, freed from grasses and plant residues, lies on top as a top layer. Thanks to the crumbler roller, the soil is reconsolidated.

All advantages at a glance

- Perfect result in one step – time saving
- Optimum seedbed preparation
- Robust construction
- Versatile use

Loader requirements

- Pressure free return
- Oil cooling
- Hydraulic capacity > 30 l/min
- Locking detent
- Speed selector recommended



Watch this attachment in use:
schaeffer.de/89-en

Width	Weight	Min. oil flow	2024	2024 SLT	2028-2	2028 SLT	23e	24e	2428-2	2428 SLT	2430	2430 SLT	2445 S	2628	2630	2630 SLT	2630 T SLT	3630	3650	3650 SLT	3650 T	3650 T SLT	4670	4670 Z	4670 T	5470 Z	5680 Z	5680 T	6680 Z	6680 T	8620 T-2	9640 T-2	9660 T-2
1,05 m	260 kg	30 l/min			□	□			□	□	■	■	■	■	□	□	□	□	□	□	□	□											
1,25 m	285 kg	30 l/min			□	□			□	□	□	□	□	□	■	■	■	■	■	■	□	□	□	□	□								

All major coupling options available. □ = good match ■ = perfect match